

Type II Enviro-Friendly Wallcovering

PHYSICAL PROPERTIES

- PVC free-eco-friendly digitally printable wallcovering
- Product Width: 54" Wide
- Construction: Polyester/Natural Fiber, 31% post-consumer recycled content
- Weight: 14 oz. per lineal yd / 9.3 oz. per square yard

ENVIRONMENTAL

- PVC and POA Free, no plasticizers, no phthalates, no formaldehyde, no chlorine, no halogen, no heavy metals, including: cadmium, mercury, lead or zinc, and no ozone depleting chemicals
- Minimum of 31% post-consumer recycled content
- Recyclable
- Breathable—high permeability rating of 66 Perms based on ASTM E96 Procedure B (wet cup)
- Made with 100% water based adhesive systems
- No harmful off-gassing
- Low VOC emitting

LEED ELIGIBILITY

Olee Creative Enviro-Friendly wall covering can contribute towards the earning of up to 7 LEED credits

- MR Credit 4.1 recycled content 10%
- MR Credit 4.2 recycled content 20%

Conditionally

- MR Credit 2.1 Contribution to project recycling program
- MR Credit 2.2 Contribution to project recycling program
- MR Credit 5.1 Manufactured local to the new construction
- EQ Credit 4.1 When installed with use of low emitting adhesives
- EQ Credit 4.6 Contribution to Low VOC emitting wall construction

AIR QUALITY

• Meets California Section IAQ 1350—Third party certified by Berkeley Analytical Associates

SPECIFICATIONS / TESTING/ CERTIFICATION

- Federal Specification: CCC-408-D Type II
- NFPA Life Safety Code 101: Meets or Exceeds

FIRE TESTING

• ASTM-E84 Tunnel Test: Class A

PROTECTIVE COATING

We apply a liquid protective coating over the ink to add these qualities to the finished wall product:

- Colorfastness
- Washability
- Scrubbability
- Abrasion Resistance
- Stain Resistance