



## OleeVue Film® Design Tips

**When designing OleeVue Film, the following tips might be helpful:**

- Film comes 48", 54" or 60" wide. Pricing will be affected by yield, and scrap incurred in each job is charged to the job, so if unfavorable yields can be avoided, prices will be more competitive.
- 1" Bleed is accounted for on all cut-to-size film sheets. So, for example, maximum finished width is 47", 53" or 59"; length is unlimited.
- If widths / lengths are larger than maximum roll size, sheets can be butt-spliced in the field by the installer. There is typically an additional charge for this installation—this can be a difficult installation and is typically avoided. Patterns can be customized to minimize over-sized surface issues. If oversized sheets must be used, call Olee Creative for a design consultation to go over best options.
- OleeVue film is available in clear (Crystal) or etch (etch or shade).
- Standard Ink colors are Glaze (faux etch), White or Shade (40% Black). Custom colors and gradients are available as custom options.
- Standard patterns are rendered at the intended scale. Production samples, which are billable, are available to approve intended scale prior to production order. All patterns can be reduced or enlarged as a custom option.
- Totally custom film can be designed as a custom pattern, or a high resolution photographic image can be printed. We have a vast stock library to select from. Client supplied images must be high-resolution, and will need to be pre-approved before production.
- All patterns and custom images can be produced so that the same image is viewable from either side of the film. The film will be applied to one side only, and the application surface will need to be noted in the specification as first surface or second surface for proper installation.
- OleeVue film is intended for indoor use. If exterior durability is required, a protective laminate can be added for an additional charge. The laminate will extend the life of the film and protect it from the elements. For heavy traffic areas, laminate can be applied in indoor applications for additional protection against wear and tear.

## OleeVue Panel® Design Tips

**When designing OleeVue Panels, the following tips might be helpful:**

- Panels come in standard 48" x 96" sheets, 1/8", 1/4" or 3/8" thick. Pricing will be affected by yield, and scrap incurred in each job is charged to the job, so if unfavorable yields can be avoided, prices will be more competitive.
- Panels can be contour cut on our router. Cutting incurs an additional charge.
- Panel edges come unfinished at 48" x 96". Finished edges can be provided, and will incur an additional charge and will cut down the size of the sheet by .5" each side.
- OleeVue standard panels are available in Polycarbonate or Acrylic. Other substrates are available.
- Standard Ink colors are Glaze (faux etch) or White. Custom colors and gradients are available as custom options.
- Standard patterns are rendered at the intended scale. Production samples are available to approve intended scale prior to production order. All patterns can be reduced or enlarged as a custom option.
- Totally custom panels can be designed as a custom pattern, or a high resolution photographic image can be printed. Any image can be printed on our panels. We have a vast stock library to select from. Client supplied images must be high-resolution, and will need to be pre-approved before production.
- All patterns and custom images can be produced so that the same image is viewable from either side of the panel. The panel will be printed on one side only, and the print surface will need to be noted in the specification as first surface or second surface for proper installation.
- OleeVue panels are intended for indoor use.
- Mounting hardware is available for an additional charge
- Fire ratings are available upon request.