

CARE & CLEANING INSTRUCTIONS

Type II Wallcovering

FOR PRODUCTS: TerralonTM Smooth Wallcovering with Liquid Overlamine Protection
TerralonTM Suede Wallcovering with Liquid Overlamine Protection

BEFORE YOU BEGIN:

It is very important that these cleaning instructions are given to your everyday maintenance staff for proper care and cleaning of your new wallcovering so it can be enjoyed for years to come!

RECOMMENDED CLEANERS: **Mild Soap & Warm Water**
2% Bleach Solution

GENERAL CLEANING:

Ordinary dirt and smudges can be removed with a mild soap and warm water. Clean from bottom of wall upward. Rinse thoroughly with clean water from the top down using a sponge. Dry wallcovering with a soft lint free cloth or towel. A 2% Bleach solution can also be used. **ALWAYS** test an inconspicuous area with any alternate or stronger detergent to be sure that the surface and ink are not damaged. **ALWAYS** respond to dirt, smudges and stains and clean area immediately to avoid allowing dirt and or stains to settle into the surface of the wallcovering.

PRECAUTIONS:

DO NOT USE active solvent type cleaning preparations, such as Virex, nail polish remover, alcohol, pine oil, or cleaners that contain these kinds of products as they can remove the image and damage the textured surface.

DO NOT USE steel wool or powdered abrasives as they can also damage the image and the textured surface.

When cleaning, always take measures to prevent water from dripping behind floor molding. The molding can be discolored and/or permanently damaged. All stains should be attempted to be removed with soap and water first. Isopropyl alcohol may set some stains that soap and water may remove.

NEVER MIX CLEANING AGENTS TOGETHER, VIOLENT REACTIONS MAY OCCUR.

IMPORTANT NOTE:

The results for the cleaners listed above does not imply a "warranty" or that the results are guaranteed. Customers should first determine if products are appropriate for use by testing a spot in an inconspicuous area as outlined above. After each application of these cleaners on the wallcovering surface, the surface must be wiped with clean water and dried with a clean towel to remove any chemical residue that could eventually discolor or degrade the material surface. Failure to follow the above dilution recommendations when using these types of cleaners or the failure to apply a clean water rinse after each application can expedite a product failure and will void any warranty claim.

CONTACT US:

For questions, please email us at sales@oleecreative.com, call **800-225-5040** or visit our website.